

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification																				
1	Section II-Bid Data Sheet, ITB 18.1	The Section II-Bid Data Sheet, ITB 18.1 is amended as under: “The Bid shall be valid until 120 days from the last date of bid submission, i.e. January 15, 2027”																				
2	Section II-Bid Data Sheet, ITB 19.3	The Section II-Bid Data Sheet, ITB 19.3 is amended as under: “The Bid security shall be valid up to 30 days beyond the bid validity period, i.e. up to February 15, 2027”																				
3	Section II-Bid Data Sheet, ITB 22.1	Section II-Bid Data Sheet, ITB 22.1 is amended as under “The Employer’s address for Bid submission is: Attention: Darjay Wangdi, Dorjilung Hydro Power Limited (DHPL), Gyalpoizhing, Mongar: Bhutan The deadline for Bid submission is: Date: September 17 2026 Time: 15.00 hrs. Bidders “shall not” have the option of submitting their Bids electronically”																				
4	Section II-Bid Data Sheet ITB 25.1	Section II-Bid Data Sheet ITB 25.1is hereby amended as “The Bid Opening shall take place at/on: Venue: Conference Hall, Dorjilung Hydro Power Limited (DHPL), Gyalpoizhing, Mongar, Bhutan Date: September 17, 2026 Time: 15.30 hrs. (Bhutan Standard Time)”																				
5	Section IX- Particular Conditions, Part B - Special Provisions	In supersession to the Request for Bids (RFB) and Addendum and Clarification-I issued for DCP-I (SN 124) under Sub-Clause 2.6 of Section IX – Particular Conditions, Part B – Special Provisions – Employer supplied Materials and Employer’s Equipment, the revised specifications of the Equipment, along with the corresponding costs are provided below: <table><tr><th>SN</th><th>Equipment</th><th>Unit</th><th>Qty.</th><th>Unit Rate</th><th>Currency</th><th>Amount</th></tr><tr><td>1</td><td>Two Boom Drill Jumbo with Basket, Brand & Model : Sandvik DT820, Number of Booms : 2xSB90(TS2-265), Basket : Operator basket for support installation/scaling (FOPS,ISO3449), Drill</td><td>No.</td><td>1</td><td>42,270,000.00</td><td>INR</td><td>42,270,000.00</td></tr></table>							SN	Equipment	Unit	Qty.	Unit Rate	Currency	Amount	1	Two Boom Drill Jumbo with Basket, Brand & Model : Sandvik DT820, Number of Booms : 2xSB90(TS2-265), Basket : Operator basket for support installation/scaling (FOPS,ISO3449), Drill	No.	1	42,270,000.00	INR	42,270,000.00
SN	Equipment	Unit	Qty.	Unit Rate	Currency	Amount																
1	Two Boom Drill Jumbo with Basket, Brand & Model : Sandvik DT820, Number of Booms : 2xSB90(TS2-265), Basket : Operator basket for support installation/scaling (FOPS,ISO3449), Drill	No.	1	42,270,000.00	INR	42,270,000.00																

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification						
			Diameter compatibility : Drifting-43-64mm, Cut hole- 76-127mm, Coverage area per set up : 110 m 2 (W14.2m X H8.4m), Feed length : > 4m, Drifter impact power : 20kw, Propulsion : Diesel drive/electric operated combination, Hydraulic Stabilizers, Control System : Automatic parallel holding, Operator Compartment: Canopy type					
		2	Side Tilt Loader, Model JCB 440-5, Bucket type – Side dumping, Engine power - 112kW@2200 rpm, Operating weight - 12.53 T Dump height - 2.7 m, Breakout force - 130kN, Steering - Articulated, Tyres - Off-road, heavy tread, Safety - ROPS/FOPS cabin, Operator compartment - Cabin type	No.	1	6,288,443.55	BTN	6,288,443.55
		3	Wet Shotcrete Machine with Robotic arm - 30 cum/hr., Spray Boom - Robotic 4-5 Axis Arm, Conveying Method – Wet Mix Pumping, Max. Pump Pressure-≥80 Bar, Nozzle Type - High-velocity	No.	1	16,544,109.20	INR	16,544,109.20

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification						
			accelerator injection, Boom Reach - ≥ 7 m vertical and ≥ 12 m horizontal, Chassis - Tyre-mounted, Safety - Dust suppression, remote control Operation and Air Compressor – Inbuilt, Model AWT3016F, Fuzhou Tuowei Mechanical & Electrical Equipment Co. Ltd., China. The cost also includes mandatory spares to be supplied along with the equipment worth INR 1,368,334.34.					
		4	Hydraulic Excavator, Model JCB 385LC with 2.1 cum bucket capacity, Engine power – 284 HP @2200 rpm, Operating weight-38.5 ton, Hydraulic pressure -343 bar, Digging depth-6.39 m and Boom reach-10.18 m.	No.	1	9,667,561.46	BTN	9,667,561.46
		5	Dumper, 30T, Model TATA SIGNA 2832.K HD BS6, 16 BOX, Dump body volume – 16 cum, Engine – Cummins ISBe 6.7LBS6, Max. power - 320HP @2300r/min, Max. Torque 1100Nm@1100-1700 r/min with PTP, Transmission - TATA G1150 9 Speed Gear	No.	6	4,139,005.65	BTN	24,834,033.90

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification						
			Box with PTO, Signa cabin with Tilt & Telescopic Steering, Tyres – 11.00-20 18 PR, Body type – Rigid, Gradeability - 30%, GVW - 28T.					
		6	Dumper, 25 T, Model TATA SIGNA 2823.TK, 6x4 BS4, Dump body volume 16 cum, Body type – rigid, Cummins Engine ISBe 5.9, Max. Engine Output - 230 HP@2500 r/min, Max. Torque-810Nm@1000-1800 r/min, No. of cylinders - 6 Inline, Engine capacity - 5883 cc, Power steering, Tyres – 11R20 radial type, Operator compartment – cabin type, GVW-28 T.	No.	2	3,694,265.85	BTN	7,388,531.70
		7	Drilling Machine – ROC, Drill hole diameter - 64-102mm, Minimum hole depth- 6m, Drill rod length- 3-4 m, Hammer Pressure - ≥21 Bar, Compressor air flow - ≥300 cfm, Tramming Speed – 2.5-4km/hr. and Compressor – Inbuilt, Model AD5SH, Swastic Drilling Co. Ltd., India	No.	2	5,768,142.86	INR	11,536,285.72
		8	Batching Plant, Output capacity – 30 cum/hr, Mixer	No.	1	4,316,046.43	INR	4,316,046.43

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification						
			type – Twin-shaft mixer, Mixer Capacity – 500 litres, Aggregate storage – 32 cum, Weighing system – Conveyor belt with load cells, Cement screw capacity – 20-25 TPH, Water metering – Automated, Control panel – PLC-based automatic control, Model MAX-30-TS, Maxmech Equipments Pvt. Ltd., India					
		9	Group Pump, Max. Pressure – 22 bar, Output capacity – 5 cum/hr., Pump type - Rotor and stator type, Max. particle size – 3mm, Mixer volume – Min. 100 litre, Agitator volume – 280 litre, Model MGP 665D, Max Spares & Engineers, India	No	1	311,397.78	INR	311,397.78
		10	Transit Mixer, Model TATA SIGNA 2823.K RMC 6S, 7cum capacity, Cummins engine ISBe 5.6 LBS6, Max. power - 164kW@2300 r/min, Max. torque- 850 NmM@1000-1700 r/min, Transmission-TATA G 950 speed Gear Box, water tank – 450 litres, Drum speed - 12-14 RPM, SIGNA cabin with Tilt & Telescopic	No.	1	4,217,483.35	BTN	4,217,483.35

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification						
			Steering, Tyre -295/95 D20(Nylon), GVW-28T.					
		11	Air Compressor (Electric), Maximum Airflow - 501 cfm, Working Pressure – 9 bar, Frequency – 50Hz, Motor Power - ≥ 75 kW, Cooling – Air-cooled, Model BADY-14..2/9, Shanghai Geso System Industrial PLC, China. The cost also includes mandatory spares to be supplied along with the equipment for INR 91,470.31	No.	1	1,378,007.21	INR	1,378,007.21
		Total Cost						128,751,900.30
		<i>Note:</i> i) A list of mandatory spares to be supplied along with equipment for Shotcrete Machine and Air Compressor and a list of spares to be bought as and when required for other equipment valid for one (1) year is shown as attached as Annexure-j(i) to j(xi) ii) Free consumables for Dumpers and Transit Mixers as Annexure k The equipment will be handed over at the site within the mobilization period and the cost will be recovered from the contractor on a pro rata basis through the Interim Payment Certificate like mobilization advance (Section IX-Particular Conditions, Part B-Special Provisions Sub-Clause 14.2(a)). The Details of the mandatory spares to be supplied along with the equipment and option to buy spares at the given rates valid for 1 year and free consumables are provided as DCP-I Annexure j(i) to j(xi) and Annexure-k.						
6	Annexure-6, Technical Specifications Section B.20, Clause 20.5.2, Page No. 542 of 745	In supersession to the Addendum and Clarification-I issued for DCP-I (SN 243), Dragon Cement (Dungsam Cement Corporation Limited), Ultratech and Dalmia Cement suppliers may be contacted for sourcing.						

**ADDENDUM AND CLARIFICATION-II for DCP-I
(Dorjilung/CPD/DCP-I/2026/1545, August 28, 2026)**

SN	RFB Clause	Addendum and Clarification
		Note: In line with Section IX-Particular Conditions, Sub-Clause 14.5 Plants and Materials intended for the works, preference shall be given to Bhutanese firms/nationals for allocation of work and procurement of materials to the extent possible.
7	Sub Clause 4.1(i) and 4.2(ii) of Section III: Evaluation and Qualification	The words “20 years” is hereby replaced with “25 years”
8	Sub-Clause 4.2(i), 4.2(ii), 4.3 (iii) and 4.2 (iv) of Section III: Evaluation and Qualification	The words “20 years” is hereby replaced with “25 years”
8	Section B.22-HSS Equipment-Technical Specification-Glasis	Steel grade E410, conforming to IS: 2062 specifications, shall be adopted for the lining of the Glacis.
9	Section B.22-HSS Equipment-Technical Specification	In supersession to Addendum and Clarification-I issued for DCP-I (SN 112), refer Annexure DCP-I(i) Technical Specifications, Sub-Clause 22.3.2: The Design Consultant shall provide the design calculations and General Arrangement drawings based on the parameters stipulated in the Technical Specification. The Bidder, through the HSS Supplier, shall prepare the Fabrication Designs and Shop Drawings, based on the design parameter stipulated in the Bidding Document, as part of their due diligence. The exact tonnage for each item shall be determined and certified in the Shop Drawings prepared by the HSS Supplier. Note: The Bidder shall submit the duly completed Technical Data in accordance with Sub-Clause 22.20 of Addendum and Clarification-I issued for DCP-I, Annexure DCP-I(i) Technical Specifications.
10	Section IX: Particular Conditions under Part B Special Provisions, Sub-Clause 1.5 Priority of Documents	Add Geotechnical Baseline Report as SN. (m) and renumber SN (m), (n), and (o) as (n), (o) and (p), respectively.